



# BATH TRIM

Version No.4

Revision Date: 30/10/2024

Page 1 of 2

## DESCRIPTION

Bath Trim is a flexible plastic extrusion which has a pressure-sensitive butyl tape applied to one side.

## KEY FEATURES

Excellent adhesion to ceramic tiles, baths and showers.

Resistant to mould growth.

The product is highly conformable.

Easy and accurate to use with little waste and no mess.

Smooth wipe-clean surface.

## USES

For sealing around baths, sinks and worktops to prevent water ingress.

## PERFORMANCE

	UNIT	NOMINAL VALUE	TEST METHOD
Dynamic Tensile Adhesion	N/cm <sup>2</sup>	25	H5
Dynamic Shear Adhesion	N/cm <sup>2</sup>	20	H15
90 ° Peel Adhesion	N/cm	12	H48
Service Temperature Range	°C	-40 to +90	

H – HS Butyl Test Method

IMPORTANT: Information, specifications, procedures and recommendations provided (“information”) are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is user’s sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user’s intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

Gordleton Industrial Park,  
Hannah Way, Sway Road,  
Lymington, Hampshire,  
SO41 8JD. UK.



T: +44 (0)1590 684400  
F: +44 (0)1590 683728  
E: sales@hsbutyl.com  
W: www.hsbutyl.com



## BATH TRIM

Version No.4

Revision Date: 30/10/2024

Page 2 of 2

### APPLICATION

#### PROPERTIES

**Application temperature range:** +5°C to +40°C

**Shelf life:** 24 months when stored flat in original packaging in cool, dry conditions.

#### INSTRUCTIONS

**Surface preparation:** All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates, HS Butyl recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the tape. Do not use white spirit or household cleaners, as these can leave a residue that will prevent the bath trim bonding to the wall or bath or worktop.

**Application:** Cut a strip long enough for the joint to be sealed. Fold the tape along the hinge. If there are to be joints at wall corners, cut a triangle off the horizontal piece, at an angle of 45° at the end where the join is to go. Remove the release film in short lengths and apply the tape to the joint, ensuring that the hinge is placed right into the back of the joint, so that when the vertical and horizontal sides bond to their respective surfaces, they lie flat against them. If this is not achieved, then the tape may not bond well to one or both surfaces. Once in place, press the tape down hard along its length in order to ensure good adhesion along the whole length.

### PACKAGING

The product is normally supplied as individually packed rolls in a clampack. Roll length and packaging specifications should be agreed prior to purchase.

Available colours: The Bath Trim is white, with white butyl.  
Other colours may be possible by arrangement.

### TOLERANCES

Rectangular sections:  
Thickness  $\pm 10\%$   
Width: up to 25mm  $\pm 1$ mm  
26mm to 100mm  $\pm 2$ mm

### GENERAL

Bath Trim is one of a range of specialist butyl products. For further information about our products, please contact our Customer Care Team or visit our Website.

**NOTE TO USER:** *by ordering/receiving product you accept the H.B. Fuller Conditions of Sale applicable in the region. Please request a copy if you have not received these or follow the link here: <https://www.hbfuller.com/en/about-us/conditions-of-sale>. These Conditions contain limits of liability and disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose). All other terms are rejected. In any event, (1) the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. (2) H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply. (3) Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence, or for breach of any mandatory implied terms unless permitted by law.*

Gordleton Industrial Park,  
Hannah Way, Sway Road,  
Lyminster, Hampshire,  
SO41 8JD. UK.



T: +44 (0)1590 684400  
F: +44 (0)1590 683728  
E: [sales@hsbutyl.com](mailto:sales@hsbutyl.com)  
W: [www.hsbutyl.com](http://www.hsbutyl.com)