



# FLEECEBAND 0318

Version No.5

Revision Date: 30/10/2024

Page 1 of 2

## DESCRIPTION

Fleeceband 0318 is a butyl tape laminated with a non-woven polyester or polypropylene fleece.

## KEY FEATURES

Good adhesion to a wide range of substrates.

Remains flexible throughout its service life.

The product is highly conformable.

Easy and accurate to use with little waste and no mess.

The fleece will accept paint, plaster, cement and adhesives.

## USES

For sealing floor-to-wall joints and around drains in wetrooms.

For sealing cracks prior to plastering.

For sound-deadening applications.

For applications to prevent air-leakage.

## PERFORMANCE

	UNIT	NOMINAL VALUE	TEST METHOD
Dynamic Shear Adhesion	N/cm <sup>2</sup>	12	H15
90° Peel Adhesion	N/cm	8	H48
180° Peel Adhesion	N/cm	9	H41
Specific Gravity	g/cm <sup>3</sup>	1.6	H6
Moisture Vapour Transmission Rate	g/m <sup>2</sup> /24hr/mm	0.18	ISO9932 / BS ISO 15106
Service Temperature Range	°C	-40 to +90	

H – HS Butyl Test Method

IMPORTANT: Information, specifications, procedures and recommendations provided (“information”) are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is user’s sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user’s intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

Gordleton Industrial Park,  
Hannah Way, Sway Road,  
Lyminster, Hampshire,  
SO41 8JD. UK.



T: +44 (0)1590 684400  
F: +44 (0)1590 683728  
E: sales@hsbutyl.com  
W: www.hsbutyl.com



## FLEECEBAND 0318

Version No.5

Revision Date: 30/10/2024

Page 2 of 2

### APPLICATION

#### PROPERTIES

**Application temperature range:** +5°C to +40°C

**Shelf life:** 24 months when stored flat in original packaging in cool, dry conditions.

#### INSTRUCTIONS

**Surface preparation:** All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates, HS Butyl recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the butyl tape. When applying the tape to porous or friable surfaces, it is recommended that the surface be treated with a suitable primer, such as an exterior grade PVA, to seal and stabilise the surface.

**Application:** Remove the release paper and apply the tape to the substrates to be joined. Take care to avoid rucks in the tape. Roll the tape with a small roller to ensure good adhesion along the whole length of the tape.

### PACKAGING

The product is normally supplied as a preformed strip on a siliconised release paper. A wide range of dimensions can be supplied. Product dimensions will determine the number of rolls per carton.

Available colours: Black or Grey

### TOLERANCES

Thickness  $\pm 10\%$

Width: up to 100mm  $\pm 2$ mm  
over 100mm  $\pm 3$ mm

### GENERAL

Fleeceband 0318 butyl tape is part of a range of butyl products for Construction market. For further information, please contact our Customer Care Team or visit our Website.

**NOTE TO USER:** *by ordering/receiving product you accept the H.B. Fuller Conditions of Sale applicable in the region. Please request a copy if you have not received these or follow the link here: <https://www.hbfuller.com/en/about-us/conditions-of-sale>. These Conditions contain limits of liability and disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose). All other terms are rejected. In any event, (1) the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. (2) H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply. (3) Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence, or for breach of any mandatory implied terms unless permitted by law.*

Gordleton Industrial Park,  
Hannah Way, Sway Road,  
Lympington, Hampshire,  
SO41 8JD. UK.



T: +44 (0)1590 684400  
F: +44 (0)1590 683728  
E: [sales@hsbutyl.com](mailto:sales@hsbutyl.com)  
W: [www.hsbutyl.com](http://www.hsbutyl.com)